

MATERIAL SAFETY DATA SHEET

OVER DRIVE Spray Buff

MSDS Ref. No: f-00248002 Date Prepared: 03/10/2003 Date Revised: 03/10/2003

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME/USE: OVER DRIVE Spray Buff

MSDS CODE: 3051381, 1479

PRODUCT CODE: 4027320, 4027324

MANUFACTURER

 The Butcher Company
 Butcher Telephone Number:
 800-225-9475

 67 Forest Street
 Emergency Telephone (24 hours):
 800-228-5635

 Marlborough, MA 01752-3012
 CHEMTREC (U.S./Can.):
 800-424-9300

 CHEMTREC (Int'l):
 +1 703-527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS#	% BY WEIGHT
Aliphatic petrolleum distillates	64742-48-9	10 - 25
Nonyl phenol ethoxylate	9016-45-9	1 - 3
Diethylene glycol ethyl ether	111-90-0	1 - 3

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations.

WHMIS CLASS: Class B- Division 3

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Opaque, White Liquid . Mild, Citrus Odor. Harmful or Fatal if Swallowed. Combustible.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(s) OF EXPOSURE: X Eye X Skin Contact Skin Absorption

X Inhalation X Ingestion

EFFECTS OF ACUTE EXPOSURE

EYES: May cause mild eye irritation. Symptoms may include redness and tearing.

SKIN: May cause mild skin irritation. Symptoms may include redness.

INHALATION: High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

INGESTION: Harmful or fatal if swallowed.

Ingestion may lead to aspiration into the lungs causing lung injury. May cause mouth, throat and stomach irritation. Symptoms may include

nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

EFFECTS OF CHRONIC EXPOSURE: Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

MEDICAL CONDITIONS AGGRAVATED: May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES: Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN: Flush thoroughly with plenty of water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops or persists. Thoroughly wash (or discard) clothing and shoes before reuse.

INHALATION: Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION: Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 67°C (152.6°F)TCC

FLAMMABLE LIMITS: Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA: Use water fog, dry chemical, CO2, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Normal products of combustion (carbon monoxide and carbon dioxide).

FIRE AND EXPLOSION HAZARDS: None known.

FIRE FIGHTING INSTRUCTIONS: Evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Ventilate spill area. Contain and isolate spill. Prevent from entering sewers and waterways. Keep non-essential personnel from entering spill area. Use mop and absorbent to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING: Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse.

STORAGE: Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Keep away from heat and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE: Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN: Where skin contact is possible, chemical-resistant clothing (e.g., gloves) should be worn.

RESPIRATORY: No respiratory protection is required if ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits may be exceeded, use appropriate respiratory protection (NIOSH)/MSHA-approved) to prevent overexposure.

ENGINEERING CONTROLS: Good general room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

EXPOSURE LIMITS:

INGREDIENT(S)	OSHA PEL/STEL	ACGIH TLV/STEL	
Aliphatic petrolleum distillates	100 ppm 400 mg/m3	g/m3 NA	
	(Naphtha)		
Nonyl phenol ethoxylate	NA	NA	
Diethylene glycol ethyl ether	NA	NA	

NA - Not Available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid ODOR: Mild, Citrus

APPEARANCE: Opaque, White

pH: 7.9 to 8.8

PERCENT VOLATILE BY WEIGHT: Not Available

VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available BOILING POINT: Not Available

FREEZING/MELTING POINT: Not Available SOLUBILITY IN WATER: Dispersible EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 0.96 VISCOSITY: Not Available

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID): Stable.

POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None.

INCOMPATIBLE MATERIALS: Oxidizers (e.g., bleach).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA: Based on testing of a similar product, this product may cause minimal to mild eye irritation and minimal skin irritation. The following data are available for product ingredients.

PRODUCT/INGREDIENT	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)	
OVER DRIVE Spray Buff	Not Available	Not Available	Not Available	
Aliphatic petrolleum distillates	5000 - mg/kg	3160 - mg/kg	Not Available	
Nonyl phenol ethoxylate	2000 - 5000	1000 - 3000 mg/kg	Not Available	
	mg/kg	1000 - 3000 Hig/kg	Not Available	
Diethylene glycol ethyl ether	5500 - 9740	8500 - mg/kg	200 - mg/L (1-hr)	
	mg/kg	8500 - 111g/kg	200 - IIIg/L (1-III)	

SENSITIZATION DATA: No data available.

CHRONIC DATA:

Prolonged overexposure to high concentrations of aliphatic petroleum distillates by inhalation has caused minor kidney effects in laboratory animals. Prolonged overexposure to high concentrations of diethylene glycol ethyl ether by ingestion has caused liver and kidney effects in

laboratory animals; prolonged overexposure by dermal absorption has also caused kidney effects in animals.

REPRODUCTIVE/TERATOGENIC DATA: No data available.

CARCINOGENIC/MUTAGENIC DATA: Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS: No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA non-hazardous waste in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated

15. REGULATORY INFORMATION

Not meant to be all-inclusive---selected regulations represented.

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed, Fire.

313 REPORTABLE INGREDIENTS: Diethylene glycol ethyl ether is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 under the chemical category Glycol Ethers.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None of the ingredients in this product are reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
Aliphatic petrolleum distillates	64742-48-9	NJ, PA
Acrylic copolymer	NA	Not Listed
Nonyl phenol ethoxylate	9016-45-9	Not Listed
Diethylene glycol ethyl ether	111-90-0	Not Listed

NA - Not Applicable

INCORPORATE (C)

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Class B-Division 3, combustible liquid. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

HMIS RATING





APPROVED BY: Product Safety & Regulatory

MSDS STATUS

Revision No: New MSDS

New MSDS

APPROVAL DATE: 03/10/2003

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.