

SAFETY DATA SHEET

Creation Date 26-Sep-2009

Revision Date 24-Dec-2021

Revision Number 5

1. Identification

Product Name Eosin Y, Alcoholic 0.25% Solution

Cat No. : SE22-500D

Synonyms Eosin yellow solution, alcoholic

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number CHEMTREC®, Inside the USA: 800-424-9300
CHEMTREC®, Outside the USA: 001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 2
Target Organs - Optic nerve, Central nervous system (CNS).	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
Causes serious eye irritation
May cause damage to organs

**Precautionary Statements****Prevention**

Wash face, hands and any exposed skin thoroughly after handling
 Do not breathe dust/fume/gas/mist/vapors/spray
 Do not eat, drink or smoke when using this product
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection

Response

If exposed or you feel unwell: Call a POISON CENTER or doctor/physician

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

WARNING. Reproductive Harm - <https://www.p65warnings.ca.gov/>.

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Ethyl alcohol	64-17-5	70.3
Water	7732-18-5	25.45
Methyl alcohol	67-56-1	3.7
Acid red 87	17372-87-1	0.3
Isopropyl alcohol	67-63-0	0.25

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial

respiration.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Notes to Physician

Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing MediaCO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.**Unsuitable Extinguishing Media**

Water may be ineffective, Do not use a solid water stream as it may scatter and spread fire

Flash Point

16.66 °C / 62 °F

Method -

No information available

Autoignition Temperature

363 °C / 685.4 °F

Explosion Limits**Upper**

19%

Lower

3.3%

Sensitivity to Mechanical Impact No information available**Sensitivity to Static Discharge** No information available**Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion ProductsCarbon monoxide (CO). Carbon dioxide (CO₂).**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
3

Flammability
3

Instability
1

Physical hazards
N/A

6. Accidental release measures

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage. Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Incompatible Materials. Acids. Acid anhydrides. Alkali metals. Metals. Ammonia. Peroxides. Isocyanates. Strong reducing agents. Strong oxidizing agents.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH	Mexico OEL (TWA)
Ethyl alcohol	STEL: 1000 ppm	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m ³ TWA: 1000 ppm TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³	STEL: 1000 ppm
Methyl alcohol	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³	TWA: 200 ppm STEL: 250 ppm
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³	TWA: 200 ppm STEL: 400 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Orange Green
Odor	Alcohol-like
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available

Flash Point	16.66 °C / 62 °F
Evaporation Rate	> 1
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	19%
Lower	3.3%
Vapor Pressure	40 mmHg @ 200 °C
Vapor Density	1.6
Specific Gravity	0.8
Solubility	miscible
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	363 °C / 685.4 °F
Decomposition Temperature	No information available
Viscosity	No information available

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions. May form explosive peroxides.
Conditions to Avoid	Heat, flames and sparks. Incompatible products. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Acids, Acid anhydrides, Alkali metals, Metals, Ammonia, Peroxides, Isocyanates, Strong reducing agents, Strong oxidizing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information	No acute toxicity information is available for this product
Oral LD50	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
Dermal LD50	Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.
Vapor LC50	Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl alcohol	LD50 = 10470 mg/kg OECD 401 (Rat) 3450 mg/kg (Mouse)	Not listed	LC50 = 117-125 mg/l (4h) OECD 403 (rat) 20000 ppm/10H (rat)
Water	-	-	-
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Acid red 87	Not listed	LD50 > 2000 mg/kg (Rat)	Not listed
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h

Toxicologically Synergistic Products	No information available
---	--------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	Irritating to eyes
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Ethanol has been shown to be carcinogenic in long-term studies only when consumed and abused as an alcoholic beverage.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl alcohol	64-17-5	Not listed	Known	A3	Not listed	A3
Water	7732-18-5	Not listed				
Methyl alcohol	67-56-1	Not listed				
Acid red 87	17372-87-1	Not listed				
Isopropyl alcohol	67-63-0	Not listed				

IARC (International Agency for Research on Cancer)

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human

Carcinogen

A1 - Known Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

A1 - Confirmed Human Carcinogen

A2 - Suspected Human Carcinogen

A3 - Confirmed Animal Carcinogen

A4 - Not Classifiable as a Human Carcinogen

A5 - Not Suspected as a Human Carcinogen

NTP: (National Toxicity Program)

ACGIH: (American Conference of Governmental Industrial Hygienists)

Mexico - Occupational Exposure Limits - Carcinogens

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Optic nerve Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl alcohol	EC50 (72h) = 275 mg/l (Chlorella vulgaris)	Fathead minnow (Pimephales promelas) LC50 = 14200 mg/l/96h	Photobacterium phosphoreum: EC50 = 34634 mg/L/30 min Photobacterium phosphoreum: EC50 = 35470 mg/L/5 min	EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h
Methyl alcohol	Not listed	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	EC50 > 10000 mg/L 24h
Acid red 87	Not listed	LC50 = 1200 mg/L/48h	Not listed	Not listed

(Oryzias latipes)				
Isopropyl alcohol	EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus)	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h

Persistence and Degradability Miscible with water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Ethyl alcohol	-0.32
Methyl alcohol	-0.74
Acid red 87	4.80
Isopropyl alcohol	0.05

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Methyl alcohol - 67-56-1	U154	-

14. Transport information

DOT

UN-No UN1987
 Proper Shipping Name ALCOHOLS, N.O.S.
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1987
 Proper Shipping Name ALCOHOLS, N.O.S.
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1987
 Proper Shipping Name ALCOHOLS, N.O.S.
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1987
 Proper Shipping Name ALCOHOLS, N.O.S.
 Hazard Class 3
 Packing Group II

15. Regulatory information

United States of America Inventory

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Ethyl alcohol	64-17-5	X	ACTIVE	-

Water	7732-18-5	X	ACTIVE	-
Methyl alcohol	67-56-1	X	ACTIVE	-
Acid red 87	17372-87-1	X	ACTIVE	-
Isopropyl alcohol	67-63-0	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA 12(b) - Notices of Export Not applicable

International Inventories

Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDSL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Ethyl alcohol	64-17-5	X	-	200-578-6	X	X	X	X	X	KE-13217
Water	7732-18-5	X	-	231-791-2	X	X		X	X	KE-35400
Methyl alcohol	67-56-1	X	-	200-659-6	X	X	X	X	X	KE-23193
Acid red 87	17372-87-1	X	-	241-409-6	X	X	X	X	X	KE-06722
Isopropyl alcohol	67-63-0	X	-	200-661-7	X	X	X	X	X	KE-29363

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)**U.S. Federal Regulations****SARA 313**

Component	CAS No	Weight %	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	3.7	1.0
Isopropyl alcohol	67-63-0	0.25	1.0

SARA 311/312 Hazard Categories See section 2 for more information

CWA (Clean Water Act) Not applicable

Clean Air Act

Component	HAPS Data	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Methyl alcohol	X		-

OSHA - Occupational Safety and Health Administration Not applicable

CERCLA Not applicable

Component	Hazardous Substances RQs	CERCLA EHS RQs
Methyl alcohol	5000 lb	-

California Proposition 65 Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage. This product contains the following Proposition 65 chemicals.

Component	CAS No	California Prop. 65	Prop 65 NSRL	Category
Ethyl alcohol	64-17-5	Development (alcoholic beverages only) Carcinogen	-	Developmental Carcinogen
Methyl alcohol	67-56-1	Developmental	-	Developmental

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Ethyl alcohol	X	X	X	X	X
Water	-	-	X	-	-
Methyl alcohol	X	X	X	X	X
Isopropyl alcohol	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
 DOT Marine Pollutant N
 DOT Severe Marine Pollutant N

U.S. Department of Homeland Security This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details)	-
Acid red 87	-	Use restricted. See item 75. (see link for restriction details)	-
Isopropyl alcohol	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl alcohol	64-17-5	Listed	Not applicable	Not applicable	Not applicable
Water	7732-18-5	Listed	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable	Not applicable
Acid red 87	17372-87-1	Not applicable	Not applicable	Not applicable	Not applicable
Isopropyl alcohol	67-63-0	Listed	Not applicable	Not applicable	Not applicable

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl alcohol	64-17-5	Not applicable	Not applicable	Not applicable	Annex I - Y42
Water	7732-18-5	Not applicable	Not applicable	Not applicable	Not applicable
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable
Acid red 87	17372-87-1	Not applicable	Not applicable	Not applicable	Not applicable
Isopropyl alcohol	67-63-0	Not applicable	Not applicable	Not applicable	Annex I - Y42

16. Other information

Prepared By Regulatory Affairs
 Thermo Fisher Scientific
 Email: EMSDS.RA@thermofisher.com

Creation Date	26-Sep-2009
Revision Date	24-Dec-2021
Print Date	24-Dec-2021
Revision Summary	This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS