

Material Safety Data Sheet

Creation Date 24-Feb-2010

Revision Date 24-Feb-2010

Revision Number 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name

Recommended Use

Cat No.

Synonyms

Company

Fisher Scientific

One Reagent Lane

Fair Lawn, NJ 07410

Tel: (201) 796-7100

Reagent Alcohol

AC611050040

Denatured Alcohol; Denatured Ethanol

Laboratory chemicals

Entity / Business Name Acros Organics One Reagent Lane Fair Lawn, NJ 07410

Emergency Telephone Number For information in the US, call: 800-ACROS-01 For information in Europe, call: +32 14 57 52

Emergency Number, Europe: +32 14 57 52 99 Emergency Number, US: 201-796-7100

CHEMTREC Phone Number, US: 800-424-9300 CHEMTREC Phone Number, Europe: 703-527-3887

2. HAZARDS IDENTIFICATION

DANGER!

Emergency Overview

Flammable liquid and vapor. Poison, may be fatal or cause blindness if swallowed. Cannot be made non-poisonous. Harmful by inhalation, in contact with skin and if swallowed. Vapor harmful. Irritating to eyes and skin. May cause irritation of respiratory tract. May cause central nervous system effects. Aspiration hazard if swallowed - can enter lungs and cause damage. This substance has caused adverse reproductive and fetal effects in humans. Substances known to cause developmental toxicity in humans. Danger of very serious irreversible effects.

Appearance Clear

Physical State Liquid

odor aromatic

Target Organs

Skin, Eyes, Central nervous system (CNS), Blood, Liver, Kidney, spleen, Optic nerve, Reproductive System

Potential Health Effects

Acute Effects Principle Routes of Exposure

| Eyes Skin Inhalation | Irritating to eyes. Irritating to skin. May be harmful in contact with skin. Harmful by inhalation. Vapor harmful. Inhalation may cause central nervous system effects. |
|------------------------------------|---|
| Ingestion | May cause irritation of respiratory tract. May be fatal or cause blindness if swallowed. Aspiration hazard. May cause central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Chronic Effects | This substance has caused adverse reproductive and fetal effects in humans. Substances known to cause developmental toxicity in humans. May cause adverse liver effects. May cause adverse kidney effects. Danger of very serious irreversible effects. |
| See Section 11 for additional Toxi | cological information. |

Aggravated Medical Conditions Central nervous system disorders. Gastrointestinal tract. Preexisting eye disorders. Liver disorders. Skin disorders.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Haz/Non-haz

Explosion Limits

| Component | CAS-No | Weight % |
|-------------------|---------|----------|
| Ethyl alcohol | 64-17-5 | 90.0 |
| Isopropyl alcohol | 67-63-0 | 5.0 |
| Methyl alcohol | 67-56-1 | 5.0 |

4. FIRST AID MEASURES

| Eye Contact | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required. |
|--------------------|---|
| Skin Contact | Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required. |
| Inhalation | Move to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a respiratory medical device. Immediate medical attention is required. |
| Ingestion | Do not induce vomiting. Call a physician or Poison Control Center immediately. |
| Notes to Physician | Treat symptomatically. |

5. FIRE-FIGHTING MEASURES

| Flash Point | 12.8 - 14.4°C / 55 - 57.9°F |
|--------------------------|-----------------------------|
| Method | No information available. |
| Autoignition Temperature | 362.8°C / 685°F |

| Upper Lower | 19 vol % 3.3 vol % |
|---|--|
| Suitable Extinguishing Media | CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Use water spray to cool unopened containers. |
| Unsuitable Extinguishing Media | Water may be ineffective. |
| Hazardous Combustion Products | No information available. |
| Sensitivity to mechanical impact Sensitivity to static discharge | No information available. No information available. |

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

| NFPA | Health 2 | Flammability 3 | Instability 0 | Physical hazards N/A |
|------------------------|------------|--|---------------------------|--------------------------------|
| | e | 5. ACCIDENTAL RELEAS | E MEASURES | |
| Personal Precaut | | Remove all sources of ignition. Use measures against static discharges | | |
| Environmental Pr | recautions | Should not be released into the environment. | | |
| Methods for Cont Up | | Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable and closed containers for disposal. | | |
| | | 7. HANDLING AND | STORAGE | |
| Handling | | Use only under a chemical fume ho | ood. Wear personal protec | tive equipment. Use explosion- |

| | proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. |
|---------|---|
| Storage | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat and sources of ignition. Flammables area. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| Engineering Measures | Use only under a chemical fume hood. Use explosion-proof |
|----------------------|--|
| | electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are |
| | close to the workstation location. |

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------|---------------|--|--|
| Ethyl alcohol | TWA: 1000 ppm | (Vacated) TWA: 1900 mg/m ³ (Vacated) TWA: 1000 ppm TWA: 1900 mg/m ³ TWA: 1000 ppm | IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³ |

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------|---------------|--|------------------------------|
| Isopropyl alcohol | TWA: 200 ppm | (Vacated) TWA: 980 mg/m ³ | IDLH: 2000 ppm |
| | STEL: 400 ppm | (Vacated) TWA: 400 ppm | TWA: 980 mg/m ³ |
| | | (Vacated) STEL: 1225 mg/m ³ | TWA: 400 ppm |
| | | (Vacated) STEL: 500 ppm | STEL: 500 ppm |
| | | TWA: 400 ppm | STEL: 1225 mg/m ³ |
| | | TWA: 980 mg/m ³ | - |
| Methyl alcohol | TWA: 200 ppm | (Vacated) TWA: 200 ppm | IDLH: 6000 ppm |
| | STEL: 250 ppm | (Vacated) TWA: 260 mg/m ³ | TWA: 200 ppm |
| | Skin | (Vacated) STEL: 325 mg/m ³ | TWA: 260 mg/m ³ |
| | | (Vacated) STEL: 250 ppm | STEL: 250 ppm |
| | | Skin | STEL: 325 mg/m ³ |
| | | TWA: 200 ppm | - |
| | | TWA: 260 mg/m ³ | |

| Component | Quebec | Mexico OEL (TWA) | Ontario TWAEV |
|-------------------|------------------------------|------------------------------|-----------------------------|
| Ethyl alcohol | TWA: 1000 ppm | TWA: 1000 ppm | TWA: 1000 ppm |
| | TWA: 1880 mg/m ³ | TWA: 1900 mg/m ³ | TWA: 1900 mg/m ³ |
| Isopropyl alcohol | TWA: 400 ppm | TWA: 400 ppm | TWA: 200 ppm |
| | TWA: 985 mg/m ³ | TWA: 980 mg/m ³ | STEL: 400 ppm |
| | STEL: 500 ppm | STEL: 1225 mg/m ³ | |
| | STEL: 1230 mg/m ³ | STEL: 500 ppm | |
| Methyl alcohol | TWA: 200 ppm | TWA: 200 ppm | TWA: 200 ppm |
| | TWA: 262 mg/m ³ | TWA: 260 mg/m ³ | TWA: 260 mg/m ³ |
| | STEL: 328 mg/m ³ | STEL: 250 ppm | STEL: 325 mg/m ³ |
| | STEL: 250 ppm | STEL: 310 mg/m ³ | STEL: 250 ppm |
| | Skin | - | Skin |

NIOSH IDLH: Immediately Dangerous to Life or Health

Personal Protective Equipment Eye/face Protection

Skin and body protection Respiratory Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166 Wear appropriate protective gloves and clothing to prevent skin exposure Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Appearance odor **Odor Threshold** рΗ Vapor Pressure Vapor Density Viscosity **Boiling Point/Range Melting Point/Range** Decomposition temperature °C Flash Point **Evaporation Rate Specific Gravity** Solubility log Pow

Liquid Clear aromatic No information available. No information available. 44 mmHa 1.24 No information available. 78.5°C / 173.3°F -114.1°C / -173.4°F No information available. 12.8 - 14.4°C / 55 - 57.9°F No information available. 0.8 Soluble in water No data available

10. STABILITY AND REACTIVITY

| Stability | Stable under normal conditions. |
|----------------------------------|---|
| Conditions to Avoid | Incompatible products. Heat, flames and sparks. |
| Incompatible Materials | Strong oxidizing agents, Strong acids, Strong bases, Metals, Acid anhydrides, Acid chlorides |
| Hazardous Decomposition Products | Carbon monoxide (CO), Carbon dioxide (CO ₂), Thermal decomposition can lead to release of irritating gases and vapors |
| Hazardous Polymerization | Hazardous polymerization does not occur |
| Hazardous Reactions . | None under normal processing. |

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information

No acute toxicity information is available for this product

Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------------|------------------|---|--|
| Ethyl alcohol | 7060 mg/kg (Rat) | Not listed | Not listed |
| Isopropyl alcohol | 4396 mg/kg (Rat) | 12800 mg/kg (Rat) 12870 mg/kg (Rabbit) | 72.6 mg/L (Rat)4 h |
| Methyl alcohol | 5628 mg/kg (Rat) | 15800 mg/kg (Rabbit) | 64000 ppm (Rat)4 h 83.2 mg/L (Rat)4 h |

Irritation

Irritating to eyes and skin

Toxicologically Synergistic Products

No information available.

Chronic Toxicity

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Component | ACGIH | IARC | NTP | OSHA | Mexico |
|-------------------|------------|---------|------------|------------|------------|
| Ethyl alcohol | Not listed | Group 1 | Not listed | Х | Not listed |
| Isopropyl alcohol | Not listed | Group 1 | Not listed | Not listed | Not listed |

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Sensitization

No information available.

Mutagenic Effects

Mutagenic effects have occurred in humans.

| Adverse reproductive effects have occurred in humans |
|---|
| Substances known to cause developmental toxicity in humans. |
| Teratogenic effects have occurred in humans |
| See actual entry in RTECS for complete information. |
| No information available |
| |

12. ECOLOGICAL INFORMATION

Ecotoxicity

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|-------------------|----------------------|----------------------------|--------------------------|-----------------------|
| Ethyl alcohol | Not listed | Leucidus idus: LC50 = 8.14 | Photobacterium | EC50 = 9268 mg/L/48h |
| | | mg/L/48h | phosphoreum:EC50 = 34634 | EC50 = 10800 mg/L/24h |
| | | | mg/L/30 min | |
| | | | Photobacterium | |
| | | | phosphoreum:EC50 = 35470 | |
| | | | mg/L/5 min | |
| Isopropyl alcohol | EC50 96 h >1000 mg/L | LC50 96 h 9640 mg/L | = 35390 mg/L EC50 | EC50 48 h 13299 mg/L |
| | EC50 72 h >1000 mg/L | | Photobacterium | |
| | EC50 96 h >1000 mg/L | | phosphoreum 5 min | |
| | | | | |
| Methyl alcohol | Not listed | Pimephales promelas: LC50 | EC50 = 39000 mg/L 25 min | EC50 > 10000 mg/L 24h |
| | | > 10000 mg/L 96h | EC50 = 40000 mg/L 15 min | |
| | | | EC50 = 43000 mg/L 5 min | |

Persistence and Degradability

No information available

No information available

Bioaccumulation/Accumulation

Mobility

| Component | log Pow |
|-------------------|---------|
| Ethyl alcohol | -0.32 |
| Isopropyl alcohol | 0.05 |
| Methyl alcohol | -0.74 |

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification

| Component | RCRA - U Series Wastes | RCRA - P Series Wastes |
|--------------------------|------------------------|------------------------|
| Methyl alcohol - 67-56-1 | U154 | - |

14. TRANSPORT INFORMATION

DOT

| | 14. TRANSPORT INFORMATION |
|---|--|
| UN-No Proper Shipping Nai Hazard Class Packing Group | UN1987 me ALCOHOLS, N.O.S. 3 II |
| TDG | |
| UN-No Proper Shipping Na Hazard Class Packing Group | UN1987 me ALCOHOLS, N.O.S. 3 II |
| IATA UN-No Proper Shipping Nar Hazard Class Packing Group | UN1987 me ALCOHOLS, N.O.S. 3 II |
| IMDG/IMO | |
| UN-No Proper Shipping Nar Hazard Class | UN1987 me ALCOHOLS, N.O.S. 3 |

15. REGULATORY INFORMATION

International Inventories

Packing Group

| Component | TSCA | DSL | NDSL | EINECS | ELINCS | NLP | PICCS | ENCS | AICS | CHINA | KECL |
|-------------------|------|-----|------|---------------|--------|-----|-------|------|------|-------|-------------------|
| Ethyl alcohol | X | Х | - | 200-578- 6 | - | | Х | Х | Х | X | KE- 13217 X |
| Isopropyl alcohol | X | Х | - | 200-661- 7 | - | | Х | Х | Х | Х | KE- 29363 X |
| Methyl alcohol | X | Х | - | 200-659- 6 | - | | Х | Х | Х | Х | KE- 23193 X |

Legend:

X - Listed

E - Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.

II

F - Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.

N - Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.

P - Indicates a commenced PMN substance

R - Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.

S - Indicates a substance that is identified in a proposed or final Significant New Use Rule

T - Indicates a substance that is the subject of a Section 4 test rule under TSCA.

XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).

Y1 - Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.

Y2 - Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b) Not applicable

SARA 313

| Component | CAS-No | Weight % | SARA 313 - Threshold Values % |
|-------------------|---------|----------|----------------------------------|
| Isopropyl alcohol | 67-63-0 | 5.0 | 1.0 |
| Methyl alcohol | 67-56-1 | 5.0 | 1.0 |

SARA 311/312 Hazardous Categorization

| Acute Health Hazard | No |
|-----------------------------------|-----|
| Chronic Health Hazard | No |
| Fire Hazard | Yes |
| Sudden Release of Pressure Hazard | No |
| Reactive Hazard | No |

Clean Water Act Not applicable

Clean Air Act

| Component | HAPS Data | Class 1 Ozone Depletors | Class 2 Ozone Depletors |
|----------------|-----------|-------------------------|-------------------------|
| Methyl alcohol | X | | - |

OSHA

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Component | Hazardous Substances RQs | CERCLA EHS RQs |
|----------------|--------------------------|----------------|
| Methyl alcohol | 5000 lb | - |

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage.

| Component | CAS-No | California Prop. 65 | Prop 65 NSRL |
|---------------|---------|---------------------|--------------|
| Ethyl alcohol | 64-17-5 | Developmental | - |
| | | | |

State Right-to-Know

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|-------------------|---------------|------------|--------------|----------|--------------|
| Ethyl alcohol | Х | Х | Х | - | Х |
| Isopropyl alcohol | Х | Х | Х | - | Х |

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|----------------|---------------|------------|--------------|----------|--------------|
| Methyl alcohol | Х | Х | Х | Х | Х |

U.S. Department of Transportation

| Reportable Quantity (RQ): | | |
|-----------------------------|---|--|
| DOT Marine Pollutant | Ν | |
| DOT Severe Marine Pollutant | Ν | |

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade

Serious risk, Grade 3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

B2 Flammable liquid D1B Toxic materials D2A Very toxic materials D2B Toxic materials



16. OTHER INFORMATION

| Prepared By | Regulatory Affairs Thermo Fisher Scientific Tel: (412) 490-8929 |
|------------------|---|
| Creation Date | 24-Feb-2010 |
| Print Date | 24-Feb-2010 |
| Revision Summary | "***", and red text indicates revision |

Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of MSDS