# SAFETY DATA SHEET

# 1. Identification

**Product identifier Liquid Wrench Penetrating Oil** 

Other means of identification

SDS number L112 L106, L112 Part No.

**Tariff code** 3403.19.5000

Recommended use Penetrating Oil **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **RSC Chemical Solutions Address** 600 Radiator Road Indian Trail, NC 28079

**United States** 

Customer Service: (704) 821-7643 **Telephone** 

Technical: (704) 684-1811

Website www.rscbrands.com E-mail sds@rscbrands.com

Emergency Telephone: **Emergency phone number** (303) 623-5716

> **Emergency Contact:** RMPDC (877) 740-5015

# 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2 **Health hazards** Acute toxicity, oral Category 4 Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard Category 1 Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

**OSHA** defined hazards Not classified.

Label elements

**Environmental hazards** 



Signal word Danger

**Hazard statement** Flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin

reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life

with long lasting effects.

Material name: Liquid Wrench Penetrating Oil

L106, L112 Version #: 09 Revision date: 10-04-2017 Issue date: 04-27-2015

# **Precautionary statement**

Prevention Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face

protection. Wear protective gloves.

IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously Response

with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Rinse mouth. Do NOT induce vomiting. If on skin: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash it before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise classified (HNOC)

Supplemental information

97.91% of the mixture consists of component(s) of unknown acute dermal toxicity. 95.11% of the mixture consists of component(s) of unknown acute inhalation toxicity.

NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in

this document. Always carefully review the entire SDS and the product label prior to use in the

workplace.

Combustible.

# 3. Composition/information on ingredients

#### **Mixtures**

| Chemical name  | Common name and synonyms | CAS number   | %         |
|--|--------------------------|--------------|-----------|
| Distillates (petroleum),<br>Hydrotreated Light                             |                          | 64742-47-8   | 70 - < 80 |
| 1,6,10-dodecatriene,<br>7,11-dimethyl-3-methylene-, (6e)-,<br>Hydrogenated |                          | 1581740-29-5 | 5 - < 10  |
| Carbon Dioxide   |                          | 124-38-9     | 1 - < 3   |
| Other components below reportable  | levels                   | _            | 10 - < 20 |

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated

clothing before reuse.

## 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

nent Firef

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame. Combustible.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not taste or swallow. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

## Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

# US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components                       | Туре | Value      |
|----------------------------------|------|------------|
| Carbon Dioxide (CAS<br>124-38-9) | PEL  | 9000 mg/m3 |

| US. OSHA Table Z-1 Limits for A | Air Contaminants (29 CFR 1910.1000) |
|---------------------------------|-------------------------------------|
| Components                      | Type                                |

| Components   | Туре       | Value       |
|--|------------|-------------|
|  |            | 5000 ppm    |
| Distillates (petroleum),<br>Hydrotreated Light (CAS<br>64742-47-8) | PEL        | 400 mg/m3   |
|  |            | 100 ppm     |
| US. ACGIH Threshold Limit Values                                   |            |             |
| Components   | Туре       | Value       |
| Carbon Dioxide (CAS 124-38-9)                                      | STEL       | 30000 ppm   |
| ,  | TWA        | 5000 ppm    |
| US. NIOSH: Pocket Guide to Chemica                                 | al Hazards |             |
| Components   | Туре       | Value       |
| Carbon Dioxide (CAS 124-38-9)                                      | STEL       | 54000 mg/m3 |
| ·  |            | 30000 ppm   |
|  | TWA        | 9000 mg/m3  |

**Biological limit values** 

Appropriate engineering

controls

No biological exposure limits noted for the ingredient(s).

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

5000 ppm

Individual protection measures, such as personal protective equipment

Face shield is recommended. Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator. Chemical respirator with organic vapor cartridge and full facepiece if

threshold limits are exceeded. Dust & vapor respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

**Appearance** Liquid Opaque

Physical state Liquid. **Form** Aerosol. Yellow Color Fragrance Odor **Odor threshold** Not available. pН Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

469.04 °F (242.8 °C) estimated

Flash point 200.0 °F (93.3 °C) Tag Closed Cup **Evaporation rate** Not available. Flammability (solid, gas) Not applicable.

Material name: Liquid Wrench Penetrating Oil

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

0.7 % estimated

Flammability limit - upper

(%)

8.5 % estimated

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.51 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 530.6 °F (277 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density 7.26 lbs/gal
Explosive properties Not explosive.

Flame extension > 18 in Flammability (flash back) No

Flammability class Combustible IIIB estimated

Heat of combustion (NFPA

30B)

36.35 kJ/g

Oxidizing properties Not oxidizing.

Percent volatile 0.29 % estimated

Specific gravity 0.87 VOC 0 %

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**Conditions to avoid**Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

Ingestion Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or

vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways.

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**US. National Toxicology Program (NTP) Report on Carcinogens** 

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful.

# 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

| Components              |                     | Species  | Test Results             |  |
|-------------------------|---------------------|--|--------------------------|--|
| Distillates (petroleum) | , Hydrotreated Ligh | it (CAS 64742-47-8)                                  |                          |  |
| Aquatic                 |                     |  |                          |  |
| Crustacea               | EC50                | Water flea (Daphnia pulex)                           | 2.7 - 5.1 mg/l, 48 hours |  |
| Fish                    | LC50                | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 2.9 mg/l, 96 hours       |  |

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

# Persistence and degradability

#### **Bioaccumulative potential**

## Partition coefficient n-octanol / water (log Kow)

1,6,10-dodecatriene, 7,11-dimethyl-3-methylene-, (6e)-, 6.08 - 6.48 OECD 117, Log Kow

Hydrogenated

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

#### DOT

Not available. **UN number** 

UN proper shipping name Consumer Commodity

Transport hazard class(es)

Class ORM-D

Subsidiary risk

Packing group Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

306 Packaging exceptions None Packaging non bulk Packaging bulk None

**IATA** 

**UN number** UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

2.1 **Class** Subsidiary risk

Not available. Packing group

**Environmental hazards** Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

**UN number** UN1950

**UN** proper shipping name Aerosols, flammable, MARINE POLLUTANT

Not established.

Transport hazard class(es)

Class 2.1 Subsidiary risk

Packing group Not available.

**Environmental hazards** 

Yes Marine pollutant F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

IATA; IMDG



## Marine pollutant



General information IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

## TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

# SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

No

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

# SARA 313 (TRI reporting)

Not regulated.

## Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### **International Inventories**

| Country(s) or region | Inventory name   | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia            | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada               | Domestic Substances List (DSL)   | No                     |
| Canada               | Non-Domestic Substances List (NDSL)                                    | Yes                    |
| China                | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe               | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe               | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                | Existing Chemicals List (ECL)  | No                     |
| New Zealand          | New Zealand Inventory  | No                     |

Country(s) or region Inventory name On inventory (yes/no)\*

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 04-27-2015 **Revision date** 10-04-2017

Version # 09

HMIS® ratings Health: 2

Flammability: 1

Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

**NFPA** ratings



**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information**This document has undergone significant changes and should be reviewed in its entirety.

Material name: Liquid Wrench Penetrating Oil

L106, L112 Version #: 09 Revision date: 10-04-2017 Issue date: 04-27-2015 9 / 9